



Reliability doesn't get a day off

The Club Car Carryall is an industry workhorse, renowned for its ease of use and day-in, day-out durability. With multiple models and accessories available, you'll find the Carryall that fits your course—and works as hard as your crew.



Standard Colors



Dark Gray White Dark Green Bright Blue

Premium Colors



Beige Classic Blue Titanium Silver Red Black

THE TOUGHEST ON TURF

Club Car's flagship turf utility vehicle, the Carryall 500, is the undisputed strongman in the Carryall line.



Brush guard



Extra-traction turf tires

OPTIONS & ACCESSORIES

More accessories available, ask your Club Car sales representative for details.



Canopy Top



Heavy-Duty Brush Guard



Stake Side Kit



Hitch



Electric Bed Lift



ROPS Cab
(Front Hinge Door)



ROPS Cab
(Rear Hinge Door)



Soft Doors



Cab Outside Mirrors



LED Headlights



EFI OVERHEAD CAM ENGINE

At the heart of Carryall hums our new power plant, sporting a 14 horsepower rated engine. The overhead cam engine with electronic fuel injection (EFI) delivers a 30% power boost and still reduces fuel consumption by up to 50%.



SAVE ON MORE THAN JUST FUEL COSTS.

- Build quality, including case-hardened steel timing chain, lowers maintenance costs
- Runs cooler, quieter, with lower emissions
- Weathers all conditions; starts fast even on the coldest mornings
- Automatically adjusts for higher altitudes
- No carburetor or choke to master or maintain
- No oil filter to change; splash lubrication reduces maintenance
- Backed by the industry's best warranty



The Carryall 300 Turf is the only utility vehicle equipped with E.R.I.C., Club's Car's advanced charging system. Efficient. Reliable. Intelligent. Connected. E.R.I.C. does it all. With cutting-edge features built into a smaller, lighter and infinitely smarter design, E.R.I.C. will have an immediate impact on your operation.



Differential Guard



Heavy Duty Batteries



Battery Capacity Indicator



5-Spoke Wheel Cover



Fuel Gauge



Cargo Tool Box



Limited Slip



Extra-Traction Turf Tires



Small Wheel Package



Locking Glove Box

Haul more gear, more securely, using VersAttach

VersAttach, the bed box rail system exclusively from Club Car, expands your payload while securing whatever's on board. Sturdy channels engineered into the walls of the cargo box accept a variety of attachments—cleats, hooks and clamps—for storing, tying down and protecting tools and gear in transit.



Bed dividers help separate and secure any size load



Add/remove/relocate clamps and tie-downs to fit your cargo



Reinforced aluminum channels can handle almost any load



A variety of equipment—cleats, hooks, clamps—is available to fit the tool and cargo



Secure expensive power tools, protecting them from transit damage



Attachment clamps are injection molded for solid fit and dependable performance



Bigger jobs, better ROI

When it comes to maximizing your investment on a hard-working vehicle, nothing fits the bill like a Carryall 700. With 1,500 pounds of capacity and almost six feet of cargo space, it handles your course's most demanding jobs, all day long.

CARRYALL 300 TURF



ELECTRIC

GASOLINE

CARRYALL 500 TURF



ELECTRIC

GASOLINE

CARRYALL 550 TURF



ELECTRIC

GASOLINE

	ELECTRIC	GASOLINE	ELECTRIC	GASOLINE	ELECTRIC	GASOLINE
ENGINE/MOTOR TYPE	48-volt DC	4-cycle	48-volt DC	4-cycle	48-volt DC	4-cycle
CONTROLLER	250 Amp - Solid state	N/A	500 Amp - Solid state	N/A	500 Amp - Solid state	N/A
DISPLACEMENT	N/A	404 cc	N/A	404 cc	N/A	404 cc
CYLINDERS	N/A	Single	N/A	Single	N/A	Single
VALVING	N/A	Overhead cam	N/A	Overhead cam	N/A	Overhead cam
COOLING	N/A	Air cooled	N/A	Air cooled	N/A	Air cooled
HORSEPOWER (RATED)	3.3 hp (2.4 kW) rated, Peak 13 hp (9.6 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940	3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940	3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940
MAX TORQUE	34.5 ft-lb (46.7 Nm) rated @ 1,980 rpm	19.91 ft-lb (27.0 Nm) rated @ 2,400 rpm	71 ft-lb (96.2 Nm) rated @ 1,450 rpm	19.91 ft-lb (27.0 Nm) rated @ 2,400 rpm	71 ft-lb (96.2 Nm) rated @ 1,450 rpm	19.91 ft-lb (27.0 Nm) rated @ 2,400 rpm
LUBRICATION	N/A	Splash lubrication	N/A	Splash lubrication	N/A	Splash lubrication
GOVERNOR	N/A	Ground speed	N/A	Ground speed	N/A	Ground speed
TRANSMISSION	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)
FRONT/REAR DIFFERENTIAL	N/A	N/A	N/A	N/A	N/A	N/A
GEAR SELECTION	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse
GEAR RATIO	12.32:1	11.47:1 forward; 15.63:1 reverse	12.32:1	11.47:1 forward; 15.63:1 reverse	12.32:1	11.47:1 forward; 15.63:1 reverse
IGNITION	N/A	Capacitive discharge	N/A	Capacitive discharge	N/A	Capacitive discharge
BATTERY	Six 8-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve
CHARGER	E.R.I.C. (650 W high frequency)	N/A	DeltaQ QuiQ (1 kW high frequency)	N/A	DeltaQ QuiQ (1 kW high frequency)	N/A
HEADLIGHTS	Two 37.5 watt halogen	Two 37.5 watt halogen	Two 37.5 watt halogen	Two 37.5 watt halogen	Two 37.5 watt halogen	Two 37.5 watt halogen
FUEL DELIVERY SYSTEM	N/A	Electronic Fuel Injection (EFI)	N/A	Electronic Fuel Injection (EFI)	N/A	Electronic Fuel Injection (EFI)
FUEL CAPACITY	N/A	5.5 gal (20.8 L)	N/A	5.5 gal (20.8 L)	N/A	5.5 gal (20.8 L)
STEERING MECHANISM	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
SUSPENSION (FRONT)	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
SUSPENSION (REAR)	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks
BRAKES	Rear mechanical drum	Rear mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock
BODY (FRONT & FINISH)	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat
BODY (FRAME & REAR)	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
TIRES (FRONT)	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply	22 x 10-10, 4-ply Turf tread; 22 x 10-10, 6-ply heavy-duty all-terrain	22 x 10-10, 4-ply Turf tread; 22 x 10-10, 6-ply heavy-duty all-terrain
TIRES (REAR)	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply	22 x 10-10, 4-ply Turf tread; 22 x 10-10, 6-ply heavy-duty all-terrain	22 x 10-10, 4-ply Turf tread; 22 x 10-10, 6-ply heavy-duty all-terrain
WHEELBASE	65.5 in (166.3 cm)	65.5 in (166.3 cm)	78.1 in (198.3 cm)	78.1 in (198.3 cm)	78.1 in (198.3 cm)	78.1 in (198.3 cm)
OVERALL HEIGHT	47.1 in (119.6 cm)	47.1 in (119.6 cm)	47.1 in (119.6 cm)	47.1 in (119.6 cm)	51.2 in (130.0 cm)	51.2 in (130.0 cm)
OVERALL LENGTH	110.1 in (279.6 cm)	110.1 in (279.6 cm)	118 in (299.7cm)	118 in (299.7cm)	118 in (299.7cm)	118 in (299.7cm)
BED L X W X H (CARGO BOX)	36.2 x 47.5 x 10.5 in (91.9 x 120.6 x 26.6 cm)	36.2 x 47.5 x 10.5 in (91.9 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)
DIFFERENTIAL GROUND CLEARANCE	5.6 in (14.2 cm)	5.2 in (13.2 cm)	5.6 in (14.2 cm)	5.2 in (13.2 cm)	6 in (15.2 cm)	6 in (15.2 cm)
TRACK WIDTH (FRONT)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	36.6 in (92.9 cm)
TRACK WIDTH (REAR)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	39.5 in (100.3 cm)
MAX WIDTH (W/O MIRRORS)	50.3 in (127.7cm)	50.3 in (127.7cm)	50.3 in (127.7cm)	50.3 in (127.7cm)	50.3 in (127.7cm)	50.3 in (127.7cm)
CURB WEIGHT (W/ BATTERIES)	1,105 lb (501.2 kg)	817 lb (370. 5 kg)	1,393 lb (631.8 kg)	907 lb (411.4 kg)	1,402 lb (635.9 kg)	942 (427.2 kg)
TOTAL VEHICLE CAPACITY	800 lb (362.8 kg)	800 lb (362.8 kg)	1,200 lb (544 kg)	1,200 lb (544 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)
BED LOAD CAPACITY	300 lb (136.0 kg)	300 lb (136.0 kg)	800 lb (362.8 kg)	800 lb (362.8 kg)	500 lb (226.7 kg)	500 lb (226.7 kg)
TOWING CAPACITY	800 lb (362.8 kg)	800 lb (362.8 kg)	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)
COMBINED GROSS VEHICLE CAPACITY	800 lb (362.8 kg)	800 lb (362.8 kg)	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)
SPEED	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)
TURNING RADIUS	108.7 in (276.2 cm)	108.7 in (276.2 cm)	119 in (302.2 cm)	119 in (302.2 cm)	126.5 in (321.3 cm)	126.5 in (321.3 cm)
WARRANTY	4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	3-year/3,000 hour limited powertrain/frame; 2-year limited remaining vehicle	4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	3-year/3,000 hour limited powertrain/frame; 2-year limited remaining vehicle	4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	3-year/3,000 hour limited powertrain/frame; 2-year limited remaining vehicle

CARRYALL 700 TURF



ELECTRIC

GASOLINE

CARRYALL 1500 4X2



GASOLINE

CARRYALL 1500 4X4



GASOLINE

DIESEL

ENGINE/MOTOR TYPE	48-volt DC	4-cycle	Kawasaki 4-cycle, industrial grade	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade
CONTROLLER	500 Amp - Solid state	N/A	N/A	N/A	N/A
DISPLACEMENT	N/A	404 cc	675 cc	675 cc	719 cc
CYLINDERS	N/A	Single	Twin-cylinder	Twin-cylinder	3-cylinder
VALVING	N/A	Overhead cam	OHV	OHV	OHV
COOLING	N/A	Air cooled	Air cooled	Air cooled	Liquid cooled
HORSEPOWER (RATED)	3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940	20.1 hp (15.0 kW) rated @ 3,400 rpm per SAE J1349	20.1 hp (15.0 kW) rated @ 3,400 rpm per SAE J1349	20.0 hp (15.0 kW) rated @ 3,600 rpm per SAE J1995
MAX TORQUE	71 ft-lb (96.2 Nm) rated @ 1,450 rpm	19.91 ft-lb (27.0 N-m) rated @ 2,400 rpm	36.5 ft/lb (49.5 Nm)	36.5 ft/lb (49.5 Nm)	33 ft/lb (45 Nm)
LUBRICATION	N/A	Splash lubrication	Full-pressure, spin-on oil filter	Full-pressure, spin-on oil filter	Full-pressure, spin-on oil filter
GOVERNOR	N/A	Ground speed	Automatic ground speed sensing	Automatic ground speed sensing	Automatic ground speed sensing
TRANSMISSION	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)	Wide ratio CVT; 3.7:1 low, 0.59:1 high	Wide ratio CVT; 3.7:1 low, 0.59:1 high	Wide ratio CVT; 3.7:1 low, 0.59:1 high
FRONT/REAR DIFFERENTIAL	N/A	N/A	Automatic locking rear differential	IntelliTrak™ Automatic 4-wheel Drive	IntelliTrak™ Automatic 4-wheel Drive
GEAR SELECTION	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse
GEAR RATIO	12.32:1	11.47:1 forward; 15.63:1 reverse	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential
IGNITION	N/A	Capacitive discharge	Transistorized magneto	Transistorized magneto	Compression
BATTERY	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve
CHARGER	DeltaQ QuiQ (1 kW high frequency)	N/A	N/A	N/A	N/A
HEADLIGHTS	Two 37.5 watt halogen	Two 37.5 watt halogen	2-55w halogen	2-55w halogen	2-55w halogen
FUEL DELIVERY SYSTEM	N/A	Electronic Fuel Injection (EFI)	Carburetor	Carburetor	Mechanical injection
FUEL CAPACITY	N/A	5.5 gal (20.8 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)
STEERING MECHANISM	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering
SUSPENSION (FRONT)	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks
SUSPENSION (REAR)	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent 4-link solid axle	Semi-independent 4-link solid axle	Semi-independent 4-link solid axle
BRAKES	4-wheel mechanical drum	4-wheel mechanical drum	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock	Mechanical disk	Mechanical disk	Mechanical disk
BODY (FRONT & FINISH)	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish
BODY (FRAME & REAR)	Aluminum	Aluminum	Tubular aluminum	Tubular aluminum	Tubular aluminum
TIRES (FRONT)	20 x 10-10, 6-ply	20 x 10-10, 6-ply	4-ply Turf; 23 x 10.5 x 12	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
TIRES (REAR)	20 x 10-10, 6-ply	20 x 10-10, 6-ply	4-ply Turf; 24 x 10.5 x 12	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
WHEELBASE	99.1 in (251.7 cm)	99.1 in (251.7 cm)	88.7 in (225.3 cm)	88.7 in (225.3 cm)	88.7 in (225.3 cm)
OVERALL HEIGHT	47.1 in (119.6 cm)	47.1 in (119.6 cm)	52.6 in (133.5 cm)	78.6 in (199.6 cm)	78.6 in (199.6 cm)
OVERALL LENGTH	137.5 in (349.3 cm)	137.5 in (349.3 cm)	124.6 in (316.5 cm)	124.6 in (316.5 cm)	124.6 in (316.5 cm)
BED L X W X H (CARGO BOX)	65.5 x 47.5 x 10.5 in (166.3 x 120.6 x 26.6cm)	65.5 x 47.5 x 10.5 in (166.3 x 120.6 x 26.6cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
DIFFERENTIAL GROUND CLEARANCE	5.6 in (14.2 cm)	5.2 in (13.2 cm)	7.3 in (18.5 cm)	8.2 in (20.8 cm)	8.2 in (20.8 cm)
TRACK WIDTH (FRONT)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
TRACK WIDTH (REAR)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
MAX WIDTH (W/O MIRRORS)	50.3 in (127.7cm)	50.3 in (127.7cm)	58.5 in (148.5 cm)	58.5 in (148.5 cm)	58.5 in (148.5 cm)
CURB WEIGHT (W/ BATTERIES)	1,475 lb (669 kg)	993 lb (450.4 kg)	1,410 lb (639.57 kg)	1,430 lbs (648.6 kg)	1,550 lbs (703.1 kg)
TOTAL VEHICLE CAPACITY	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)	1,450 lb (658 kg)/1,900 lb (862 kg)*	1,200 lb (544 kg)/1,450 lb (658 kg)**	1,200 lb (544 kg)/1,450 lb (658 kg)**
BED LOAD CAPACITY	1,000 lb (453.5 kg)	1,000 lb (453.5 kg)	1,050 lb (476.3 kg)/1,500 lb (680.3 kg)*	800 lb (363.2 kg)/1,050 lb (658 kg)**	800 lb (363.2 kg)/1,050 lb (658 kg)**
TOWING CAPACITY	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)	1,450 lb (658 kg)/1,900 lb (862 kg)*	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)
COMBINED GROSS VEHICLE CAPACITY	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)	1,450 lb (658 kg)/1,900 lb (862 kg)*	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)
SPEED	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)	19 mph (30.6 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)
TURNING RADIUS	162.8 in (413.4 cm)	162.8 in (413.4 cm)	150.5 in (382.3 cm)	150.5 in (382.3 cm)	150.5 in (382.3 cm)
WARRANTY	4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	3-year/3,000 hour limited powertrain/frame; 2-year limited remaining vehicle	2-year/2,000 hour limited	2-year/2,000 hour limited	2-year/2,000 hour limited

*3/4-ton option; ** High-capacity option

Visit clubcar.com for more on Carryall's warranty.

CARRYALL 1500 4X4 INTELLITACH



DIESEL

CARRYALL 1700 4X4



GASOLINE

DIESEL

ENGINE/MOTOR TYPE	<i>Kubota D722, industrial grade</i>	<i>Kawasaki 4-cycle, industrial grade</i>	<i>Kubota D722, industrial grade</i>
CONTROLLER	N/A	N/A	N/A
DISPLACEMENT	719 cc	675 cc	719 cc
CYLINDERS	3-cylinder	Twin-cylinder	3-cylinder
VALVING	OHV	OHV	OHV
COOLING	Liquid cooled	Air cooled	Liquid cooled
HORSEPOWER (RATED)	20.0 hp (15.0 kW) rated @ 3,600 rpm per SAE J1995	20.1 hp (15.0 kW) rated @ 3,400 rpm per SAE J1349	20.0 hp (15.0 kW) rated @ 3,600 rpm per SAE J1995
MAX TORQUE	33 ft/lb (45 Nm)	36.5 ft/lb (49.5 Nm)	33 ft/lb (45 Nm)
LUBRICATION	Full-pressure, spin-on oil filter	Full-pressure, spin-on oil filter	Full-pressure, spin-on oil filter
GOVERNOR	Automatic ground speed sensing	Automatic ground speed sensing	Automatic ground speed sensing
TRANSMISSION	Wide ratio CVT; 3.7:1 low, 0.59:1 high	Wide ratio CVT; 3.7:1 low, 0.59:1 high	Wide ratio CVT; 3.7:1 low, 0.59:1 high
FRONT/REAR DIFFERENTIAL	IntelliTrak™ Automatic 4-wheel Drive	IntelliTrak™ Automatic 4-wheel Drive	IntelliTrak™ Automatic 4-wheel Drive
GEAR SELECTION	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse
GEAR RATIO	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential
IGNITION	Compression	Transistorized magneto	Compression
BATTERY	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve
CHARGER	N/A	N/A	N/A
HEADLIGHTS	2-55w halogen	2-55w halogen	2-55w halogen
FUEL DELIVERY SYSTEM	Mechanical injection	Carburetor	Mechanical injection
FUEL CAPACITY	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)
STEERING MECHANISM	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering
SUSPENSION (FRONT)	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks
SUSPENSION (REAR)	Semi-independent 4-link solid axle	Semi-independent 4-link solid axle	Semi-independent 4-link solid axle
BRAKES	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk
PARK BRAKE	Mechanical disk	Mechanical disk	Mechanical disk
BODY (FRONT & FINISH)	GE Gelyo high-impact, scratch-resistant, injection molded color, automotive finish	GE Gelyo high-impact, scratch-resistant, injection molded color, automotive finish	GE Gelyo high-impact, scratch-resistant, injection molded color, automotive finish
BODY (FRAME & REAR)	Tubular aluminum	Tubular aluminum	Tubular aluminum
TIRES (FRONT)	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
TIRES (REAR)	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
WHEELBASE	88.7 in (225.3 cm)	114 in (225.3 cm)	114 in (225.3 cm)
OVERALL HEIGHT	78.6 in (199.6 cm)	78.6 in (199.6 cm)	78.6 in (199.6 cm)
OVERALL LENGTH	148.6 in (377.4 cm)	157.6 in (400.3 cm)	157.6 in (400.3 cm)
BED L X W X H (CARGO BOX)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
DIFFERENTIAL GROUND CLEARANCE	8.2 in (20.8 cm)	8.2 in (20.8 cm)	8.2 in (20.8 cm)
TRACK WIDTH (FRONT)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
TRACK WIDTH (REAR)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
MAX WIDTH (W/O MIRRORS)	58.5 in (148.5 cm)	58.5 in (148.5 cm)	58.5 in (148.5 cm)
CURB WEIGHT (W/ BATTERIES)	1,710 lb (775.64 kg)	1,630 lb (739.36 kg)	1,750 lb (793.8 kg)
TOTAL VEHICLE CAPACITY	1,700 lb (771.1 kg)	1,600 lb (725.8 kg)	1,600 lb (725.8 kg)
BED LOAD CAPACITY	800 lb (363.2 kg)	800 lb (363.2 kg)	800 lb (363.2 kg)
TOWING CAPACITY	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)
COMBINED GROSS VEHICLE CAPACITY	1,800 lb (816.5 kg)	1,800 lb (816.5 kg)	1,800 lb (816.5 kg)
SPEED	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)
TURNING RADIUS	160 in (406.4 cm)	206.5 in (524.5 cm)	206.5 in (524.5 cm)
WARRANTY	2-year/2,000 hour limited	2-year/2,000 hour limited	2-year/2,000 hour limited

Visit clubcar.com for more on Carryall's warranty.